

SAFETY DATA SHEET

Based on Regulation (EC) No 1907/2006 (REACH) Article 31 and Annex II

SOLBERG 1X3 ATC 1%-3%

1. Identification of the substance/preparation and of the company/undertaking

1.1 Identification of the substance or preparation:

Product name : SOLBERG 1X3 ATC 1%-3%
Synonyms : none

CAS No. : N.A.
EC index No. : N.A.
EINECS No. : N.A.
RTECS No. : N.A.

NFPA code : N.D.
Molecular weight : N.A.
Formula : N.A.

1.2 Use of the substance/preparation:

Fire extinguishing medium: concentrate

1.3 Company/undertaking identification:

SOLBERG SCANDINAVIAN AS - NORWAY
Olsvollstranda
NO-5938 Sæbøvågen
Tel: +47 56 34 97 00
Fax: +47 56 34 97 01
e-mail address: Luc@arcticfoam.com

1.4 Emergency telephone:

+47 97 64 00 00 (24h/24h)
SOLBERG SCANDINAVIAN AS - NORWAY

2. Hazards identification

- Irritating to eyes

3. Composition/information on ingredients

| Hazardous ingredients | CAS No. EINECS/ELINCS No. | Conc. (%) | Hazards (R-phrases) | Hazard symbol |
|--|------------------------------|-----------|------------------------|------------------|
| 2-(2-butoxyethoxy) ethanol | 112-34-5 203-961-6 | <20 | 36 (1) (2) | Xi |
| sodium decyl sulphate | 142-87-0 205-568-5 | <5 | 22-38-41 (1) | Xn |
| 1-propanaminium, N-(3-aminopropyl)-2-hydroxy-N,N-dimethyl-3-sulfo-, N-coco acyl derivs., hydroxides, inner salts | 68139-30-0 268-761-3 | <2.5 | 36/38-51/53 (1) | Xi;N |
| D-glucopyranose, oligomers, decyl octyl glycosides | 68515-73-1 500-220-1 | <5 | 41 (1) | Xi |
| sucrose | 57-50-1 200-334-9 | >1 | - (2) | - |
| thiols, C8-20, gamma-omega-perfluoro-, telomers with acrylamide | 70969-47-0 - | <5 | - | - |
| N-[3-(dimethylamino)propyl]-3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctanesulphonamide N-oxide | 80475-32-7 279-481-6 | <1 | 52/53 (1) | - |

(1) For R-phrases in full: see heading 16

(2) Substance with a Community workplace exposure limit

(3) PBT-substance

Printing date : 04-2008
Compiled by : Brandweerinformatiecentrum voor Gevaarlijke Stoffen vzw (BIG)
Technische Schoolstraat 43 A, B-2440 Geel
☎ +32 14 58 45 47 http://www.big.be e-mail address: info@big.be

1/9

Date of issue : 18-03-2008
Reference number : BIG\45976GB
Reason for revision :
Revision :
Revision number : 000

SOLBERG 1X3 ATC 1%-3%

4. First aid measures

- 4.1 After inhalation:**
- Remove the victim into fresh air
 - Respiratory problems: consult a doctor/medical service
- 4.2 Skin contact:**
- Rinse with water
 - Soap may be used
 - Take victim to a doctor if irritation persists
- 4.3 Eye contact:**
- Rinse immediately with plenty of water
 - Take victim to an ophthalmologist if irritation persists
- 4.4 After ingestion:**
- Rinse mouth with water
 - Immediately give lots of water to drink
 - Consult a doctor/medical service if you feel unwell

5. Fire-fighting measures

- 5.1 Suitable extinguishing media:**
- For surrounding fires: all extinguishing media allowed
- 5.2 Unsuitable extinguishing media:**
- No data available
- 5.3 Special exposure hazards:**
- On burning: release of toxic and corrosive gases/vapours (nitrous vapours, carbon monoxide - carbon dioxide)
- 5.4 Instructions:**
- Dilute toxic gases with water spray
- 5.5 Special protective equipment for fire-fighters:**
- Heat/fire exposure: compressed air/oxygen apparatus
 - Gloves

6. Accidental release measures

- 6.1 Personal precautions:**
See heading 8.2/13
- 6.2 Environmental precautions:**
- Contain released substance, pump into suitable containers
 - Plug the leak, cut off the supply
- 6.3 Methods for cleaning up:**
- Take up liquid spill into inert absorbent material, e.g.: sand/earth
 - Scoop absorbed substance into closing containers
 - Clean contaminated surfaces with an excess of water
 - Wash clothing and equipment after handling

SOLBERG 1X3 ATC 1%-3%

7. Handling and storage

7.1 Handling:

- Observe normal hygiene standards

7.2 Storage:

- Keep container in a well-ventilated place
- Meet the legal requirements
- Keep away from: heat sources

| | | |
|-------------------------|---------------------|------|
| Storage temperature | : -30/50 | °C |
| Quantity limits | : N.D. | kg |
| Storage life | : N.D. | days |
| Materials for packaging | : | |
| - suitable | : no data available | |
| - to avoid | : no data available | |

7.3 Specific use(s):

- See information supplied by the manufacturer for the identified use(s)

8. Exposure controls/Personal protection

8.1 Exposure limit values:

8.1.1 Occupational exposure:

2- (2-butoxyethoxy) ethanol

| | | | | |
|-----------------|---------|-------------------|----|-----|
| TLV-TWA | : | mg/m ³ | | ppm |
| TLV-STEL | : | mg/m ³ | | ppm |
| WEL-LTEL | : 67.5 | mg/m ³ | 10 | ppm |
| WEL-STEL | : 101.2 | mg/m ³ | 15 | ppm |
| TRGS 900 | : 100 | mg/m ³ | | ppm |
| MAK | : 100 | mg/m ³ | | ppm |
| MAC-TGG 8 h | : 50 | mg/m ³ | | |
| MAC-TGG 15 min. | : 100 | mg/m ³ | | |
| VME-8 h | : | mg/m ³ | | ppm |
| VLE-15 min. | : | mg/m ³ | | ppm |
| GWBB-8 h | : 67.5 | mg/m ³ | 10 | ppm |
| GWK-15 min. | : 101.2 | mg/m ³ | 15 | ppm |
| EC | : 67.5 | mg/m ³ | 10 | ppm |
| EC-STEL | : 101.2 | mg/m ³ | 15 | ppm |

SOLBERG 1X3 ATC 1%-3%

sucrose

| | | | | |
|-----------------|------|-------------------|---|-----|
| TLV-TWA | : 10 | mg/m ³ | | ppm |
| TLV-STEL | : - | mg/m ³ | | ppm |
| WEL-LTEL | : 10 | mg/m ³ | - | ppm |
| WEL-STEL | : 20 | mg/m ³ | - | ppm |
| TRGS 900 | : | mg/m ³ | | ppm |
| MAK | : | mg/m ³ | | ppm |
| MAC-TGG 8 h | : | mg/m ³ | | |
| MAC-TGG 15 min. | : | mg/m ³ | | |
| VME-8 h | : 10 | mg/m ³ | - | ppm |
| VLE-15 min. | : - | mg/m ³ | - | ppm |
| GWBB-8 h | : 10 | mg/m ³ | - | ppm |
| GWK-15 min. | : - | mg/m ³ | - | ppm |
| EC | : | mg/m ³ | | ppm |
| EC-STEL | : | mg/m ³ | | ppm |

8.1.2 Sampling methods:

- Sucrose (see Dust, Total or Dust, Respirable nuisance) OSHA CSI

8.2 Exposure controls:

8.2.1 Occupational exposure controls:

- Measure the concentration in the air regularly
- Work under local exhaust/ventilation

Personal protective equipment:

a) Respiratory protection:

- Wear gas mask with filter type A if conc. in air > exposure limit

b) Hand protection:

- Gloves
- Suitable materials: No data available
- Breakthrough time: N.D.

c) Eye protection:

- Safety glasses

d) Skin protection:

- Protective clothing
- Suitable materials: No data available

8.2.2 Environmental exposure controls: see headings 6.2, 6.3 and 13

9. Physical and chemical properties**9.1 General information:**

Appearance (at 20°C) : Liquid
Odour : Pleasant
Colour : Brown-yellow

9.2 Important health, safety and environmental information:

pH value (at 100%) : 8
Boiling point/boiling range : 100 °C
Flash point/flammability : > 100 °C
Explosion limits (explosive properties) : N.D. vol%
Oxidising properties : N.D.
Vapour pressure (at 20°C) : N.D. hPa
Vapour pressure (at 50°C) : N.D. hPa
Relative density (at 20°C) : 1.09
Water solubility : COMPLETELY
Soluble in : No data available
Relative vapour density : N.D.
Viscosity (at °C) : N.D. Pa.s
Partition coefficient n-octanol/water : N.D.
Evaporation rate
ratio to butyl acetate : N.D.
ratio to ether : N.D.

9.3 Other information:

Melting point/melting range : -8 °C
Auto-ignition temperature : N.D. °C
Saturation concentration : N.D. g/m³
Specific conductivity : N.D. pS/m

10. Stability and reactivity**10.1 Conditions to avoid:**

- Stable under normal conditions

10.2 Materials to avoid:

- Keep away from: heat sources

10.3 Hazardous decomposition products:

- On burning: release of toxic and corrosive gases/vapours (nitrous vapours, carbon monoxide - carbon dioxide) and formation of small quantities of sulphur oxides, hydrofluoric acid, hydrogen chloride

11. Toxicological information**11.1 Acute toxicity:**

2-(2-butoxyethoxy) ethanol
LD50 oral rat : 5660 mg/kg
LD50 dermal rabbit : 2700 mg/kg

sodium decyl sulphate
LD50 oral rat : 1950 mg/kg

sucrose
LD50 oral rat : 29700 mg/kg

11.2 Chronic toxicity:

2-(2-butoxyethoxy) ethanol
Teratogenicity (MAK) : C

sucrose
Carcinogenicity (TLV) : A4

11.3 Routes of exposure: ingestion, inhalation, eyes and skin

11.4 Acute effects/symptoms:

AFTER EYE CONTACT
- Redness of the eye tissue
- Irritation of the eye tissue

11.5 Chronic effects:

- Contains a substance of group C (MAK-Schwangerschaftsgruppe) (2-(2-butoxyethoxy) ethanol: no teratogenic risk at exposure level lower than MAK value)

12. Ecological information**12.1 Ecotoxicity:****2- (2-butoxyethoxy) ethanol:**

- LC50 (96 h) : 1300 ppm (LEPOMIS MACROCHIRUS)
- EC50 (48 h) : >100 mg/l (DAPHNIA MAGNA)
- EC50 (192 h) : 53 mg/l (ALGAE)

- **Effect on waste water purification** : no data available

12.2 Mobility:

- **Volatile organic compounds (VOC):** < 1%
- Soluble in water

For other physicochemical properties see heading 9

Maximum concentration in drinking water: 200 mg/l (sodium) (Directive 98/83/EC)

12.3 Persistence and degradability:

- **biodegradation BOD₅** : N.D. % ThOD
- **water** : -
- **soil** : T ½: N.D. days
- contains persistent organic fluorocomponent(s)

12.4 Bioaccumulative potential:

- **log P_{ow}** : N.D.
- **BCF** : N.D.

12.5 Results of PBT assessment:

- Not applicable, based on available data.

12.6 Other adverse effects:

- **WGK** : 1 (Classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 17 May 1999)
- **Effect on the ozone layer** : Not dangerous for the ozone layer (1999/45/EC)
- **Greenhouse effect** : no data available

13. Disposal considerations**13.1 Provisions relating to waste:**

- Waste material code (91/689/EEC, Council Decision 2001/118/EC, O.J. L47 of 16/2/2001): 07 06 03* (organic halogenated solvents, washing liquids and mother liquors)
- LWCA (the Netherlands): KGA category 04
- Hazardous waste (91/689/EEC)

13.2 Disposal methods:

- Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber with energy recovery
- Contains an organic halogen which may add to the AOX value
- Contains a component for which a prohibition exists against discharge into surface water

13.3 Packaging/Container:

- Waste material code packaging (91/689/EEC, Council Decision 2001/118/EC, O.J. L47 of 16/2/2001): 15 01 10* (packaging containing residues of or contaminated by dangerous substances)

14. Transport information

- 14.1 Classification of the substance in compliance with UN Recommendations
 UN number : -
 CLASS :
 SUB RISKS :
 PACKING GROUP :
- 14.2 ADR (transport by road)
 CLASS : Not subject
 PACKING GROUP :
 CLASSIFICATION CODE :
 DANGER LABEL TANKS :
 DANGER LABEL PACKAGES :
 PROPER SHIPPING NAME :
- 14.3 RID (transport by rail)
 CLASS : Not subject
 PACKING GROUP :
 CLASSIFICATION CODE :
 DANGER LABEL TANKS :
 DANGER LABEL PACKAGES :
 PROPER SHIPPING NAME :
- 14.4 ADN (transport by inland waterways)
 CLASS : Not subject
 PACKING GROUP :
 CLASSIFICATION CODE :
 DANGER LABEL TANKS :
 DANGER LABEL PACKAGES :
- 14.5 IMDG (maritime transport)
 CLASS : Not subject
 SUB RISKS :
 PACKING GROUP :
 MFAG :
 EMS :
 MARINE POLLUTANT :
- 14.6 ICAO (air transport)
 CLASS : Not subject
 SUB RISKS :
 PACKING GROUP :
 PACKING INSTRUCTIONS PASSENGER AIRCRAFT :
 PACKING INSTRUCTIONS CARGO AIRCRAFT :
- 14.7 Special precautions : not restricted for any mode of international transport

15. Regulatory information

15.1 EU legislation:

Classification according to directives 67/548/EEC, 1999/45/EC and 2006/8/EC



Irritant

- R36 : Irritating to eyes
 S(02) : (Keep out of reach of children)
 S(46) : (If swallowed, seek medical advice immediately and show this container or label)

15.2 National provisions:

The Netherlands:

Waterbezwaarlijkheid: 11

Germany:

WGK : 1 (Classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 17 May 1999)

16. Other information

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

N.A. = NOT APPLICABLE
N.D. = NOT DETERMINED
(*) = INTERNAL CLASSIFICATION (NFPA)

PBT-substances = persistent, bioaccumulative and toxic substances

Exposure limits:

TLV : Threshold Limit Value - ACGIH USA
WEL : Workplace Exposure Limits - United Kingdom
TRGS 900 : Technische Regel für Gefahrstoffe 900 (Arbeitsplatzgrenzwerte) - Germany
MAK : Maximale Arbeitsplatzkonzentrationen - Germany
MAC : Maximale aanvaarde concentratie - The Netherlands
VME : Valeurs limites de Moyenne d'Exposition - France
VLE : Valeurs limites d'Exposition à court terme - France
GWBB : Grenswaarde beroepsmatige blootstelling - Belgium
GWK : Grenswaarde kortstondige blootstelling - Belgium
EC : Indicative occupational exposure limit values - directive 2000/39/EC

I : Inhalable fraction = T: Total dust = E: Einatembarer Aerosolanteil
R : Respirable fraction = A: Alveolengängiger Aerosolanteil/Alveolar dust
C : Ceiling limit

Chronic toxicity:

K : List of the carcinogenic substances and processes - The Netherlands

Full text of any R phrases referred to under headings 2 and 3:

R22 : Harmful if swallowed
R36 : Irritating to eyes
R36/38 : Irritating to eyes and skin
R38 : Irritating to skin
R41 : Risk of serious damage to eyes
R51/53 : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R52/53 : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment