

PAC FIRE NL9723ES



STRUCTURAL FIRE FIGHTING HOOD

FABRIC

CONTENT: 20% Nomex 80% Lenzing FR
CONSTRUCTION: 1 x 1 Rib Knit
WEIGHT: 8 ounces per sq. yd. (240grms)
STRETCH: 100%

HEAD DESIGN

STYLE: Separate head with sewn on back and front bib.
LAYERS: Two
LENGTH: 13 inches (32cm)
WIDTH: Top of face opening to back seam: 8.5 inches (21cm)
Middle of face opening to back seam: 6.5 inches (16cm)
Bottom of face opening to back seam: 10.5 inches (26cm)

CROWN AREA

Four inches (10cm) from top of crown to top of face opening.



BIB DESIGN

Style:

A two-piece double layer yoke style bib is sewn to the head and forms a neck seam. The back bib extends eight inches (20cm) down the back. The front bib extends six inches (15cm) down the front. The front and back bibs are joined at the shoulder to form a three-inch shoulder seam on either side of the head.

FACE OPENING

Face opening sewn with half inch elastic
Relaxed measurement: 5 to 5 ½ inches (14cm)
Fully stretched: exceeds 15 inches (38cm)

CONSTRUCTION

All seams will conform to those stitch types specified in ASTM D6193

MAJOR SEAMS: Initial seam sewn with Stitch Type 504 and then sewn over flattened with Stitch Type 605.

OPTIONAL HEAD SEAM: Flat lock seam sewn with Stitch Type 607.

FACE OPENING: Elastic is sewn to edge of face opening with Stitch Type 504, turned under and over-seam with Stitch Type 402 to totally cover elastic.

BINDING: One and a half inch (3.75cm) binding is sewn to hem through folder with Stitch Type 402 to create a ½ inch (1.3cm) finished bound hem.

THREAD: 100% Nomex; UL component recognised to NFPA 1971-2007 edition.

CERTIFICATION

Classified by Underwriters Laboratories to meet NFPA Standard 1971-2007 edition.
ISO9001:2000



PAC FIRE AUSTRALIA

**Unit 1, 28 Burnside Road,
Hallmarc Business Park, YATALA QLD 4207**

Phone 1300 73 1800

Fax: (07) 3441 7177

Email: sales@pacfire.com.au

Website: www.pacfire.com.au