

NL12SE WILDLAND



SINGLE LAYER NOMEX HOOD

FABRIC

CONTENT: 100% NOMEX
CONSTRUCTION: Interlock
WEIGHT: 6.5 oz sq. yd (185grms)
STRETCH: 65%

HEAD DESIGN

STYLE: Separate head with sewn on back and front bib.
LAYERS: One
LENGTH: 12 inches (30cm)
WIDTH: Top of face opening to back seam: 9 inches (24cm)
Middle of face opening to back seam: 7 inches (18cm)
Bottom of face opening to back seam: 11 inches (27cm)
CROWN AREA Three inches (7.5cm) from top of crown to top of face opening.



BIB DESIGN

STYLE: A two-piece single layer yoke style bib is sewn to the head and forms a neck seam. The back bib extends six inches (15cm) down the back. The front bib extends six inches (15cm) down the front. The front and back bibs are joined at the shoulder to form a three-inch (7.5cm) shoulder seam on either side of the head.

FACE OPENING

Face opening sewn with 3/16 inch elastic channeled in binding.

Relaxed measurement: 3 inches (7.5cm) high in centre, 6 ³/₄ inches (16cm) wide.

Fully stretched: exceeds 13 inches (32cm)

CONSTRUCTION

All seams will conform to those stitch types specified in ASTM D6193

THREAD: 100% NOMEX

FLAME RESISTANCE: Method 5903.1, Flame Resistance of cloth; vertical, of Federal Test Methods Standard 191A, Textile Test Methods, is used.

RESULTS BEFORE WASH: After Flame 0.3 sec./ After Glow 11.4 sec./ Char Length 1.5 in./ No Drip

RESULTS AFTER WASH: After Flame 0.5 sec./ After Glow 13.7 sec./ Char Length 1.4 in./ No Drip

CERTIFICATION

ISO9001:2000



PAC FIRE AUSTRALIA

**Unit 1, 28 Burnside Road,
Hallmarc Business Park, YATALA QLD 4207**

Phone 1300 73 1800

Fax: (07) 3441 7177

Email: sales@pacfire.com.au

Website: www.pacfire.com.au