



LOW EXPANSION 2010 PATENTED FOAM NOZZLES and FOAM TUBES

POK offers a wide NEW range of water / foam low expansion nozzles and tubes with a durable, lightweight constant gallonage nozzle with flow reachover 275+ feet with an expansion ration of 10+. Made out of high-grade aluminum alloy with the trademarked NITUFF™ finish that gives 50 microns of PTFE impregnated anodized with a red epoxy finish. Any hose line can benefit from these tubes and increase their performance and reach with water or with a foam solution. Patented System.

60 GPM / 200 l/mn
Reach at 75 PSI : 23 m

95 GPM / 400 l/mn
Reach at 75 PSI : 35 m



200 GPM / 800 l/mn
Reach at 75 PSI : 40 m



400 GPM / 1500 l/mn
Reach at 100 PSI : 45 m



500 GPM / 2000 l/mn
Reach at 100 PSI : 60 m

1300 GPM / 5000 l/mn
Reach at 100 PSI : 75 m

1600 GPM / 6000 l/mn
Reach at 100 PSI : 85 m



Low Expansion Foam Nozzles

Flow (l/min/GPM)	Inlet / Weight	Code
200 / 60	Storz 1.5" - 1.89 Kg	25046
200 / 60	1.5" F Inlet - 1.85 Kg	24117
400 / 95	Storz 1.5" - 1.91 Kg	25047
400 / 95	1.5" F Inlet - 1.87 Kg	24121
800 / 200	Storz 2.5" - 2.94 Kg	25048
800 / 200	2.5" F inlet - 2.92 Kg	24125

**+30%
Better
Performance**

Low Expansion Foam Tubes

Flow (l/min/GPM)	Inlet / Weight	Code
800 / 200	G 1.5" inlet - 1.3 Kg	24174
1500 / 400	G 2.5" inlet - 3.0 Kg	23989
2000 / 500	G 2.5" inlet - 3.0 Kg	24038
3000 / 800	3.5" F inlet - 6.0 Kg	24042
4000 / 1050	3.5" F inlet - 6.0 Kg	24046
5000 / 1300	3.5" F inlet - 6.0 Kg	24169
6000 / 1600	3.5" F inlet - 10.3 Kg	24079