

## FLAT-FORM LIFTING BAGS 8.0 bar

Flat Bags are perfected standard lifting bags. Due to the construction the entire bag surface lifts evenly providing a constant lifting force independent of the lifting height.

The levelled bag surface provides a larger contact surface and an improved safety during use, especially when two or even three bags are placed one top of each other.

These bags are made from an excellent wear resistant rubber compound and are Kevlar kord reinforced.

The lifting performance graphs, which with the classic lifting bags sometimes were rather complicated, are therefore no longer required.



528134



### Flat Bags 8.0 bar

#### Technical data

Model	EU	SFB-K 7/17	SFB-K 11/17	SFB-K 18/19	SFB-K 32/19
Art. Number		519883	519884	519885	519886
Size	cm x cm	55x55	61x61	78x78	91x91
Thickness	mm	28	28	28	28
Weight	kg	8	10.6	17.1	23.8
Insertion height	mm	30	30	30	30
Max. lifting height	cm	17	17	19	19
Max. lifting capacity	kg	20250	24690	41285	65900
Max. lifting capacity at max. lifting height	kg	6728	10952	17672	31752
Size of flat area at max. lifting height	cm x cm	29x29	37x37	47x47	63x63
Nominal content	l	24.0	40.0	90.0	145.0
Max. air requirement	l	224	350	740	1305
Max. inflation pressure	bar	8	8	8	8
Inflation time	sec	13.0	17.0	43.0	65.0
Connection piece	colour	Yellow	Yellow	Orange	Orange

529480 (yellow)



530543 (orange)



529481 (yellow)

530545 (orange)