

187 Forestry Hose - Type 8F

Polyester Single Jacket Forestry Hose

Performance Features:

Snap-tite 8F Type 187 forestry hose is a lightweight, all-synthetic fire hose with a polyurethane lining inside a polyester jacket designed to meet the USDA Forest Service specification 5100-187 for "Synthetic Lined" fire hose. The optional Dura-Cote™ treatment greatly increases abrasion, heat, and flame resistance while virtually eliminating water pick-up. When used, 8F meets the new "Type II" specification, is protected from mildew and no drying is required. This hose is available in 50' or 100' lengths, includes aluminum rocker lug or ¼ turn forestry couplings, and meets or exceeds the low weight requirements of the specifications.

How to Order

8F	10X50		Y	10	N	
TYPE	HOSE I.D.	x HOSE LENGTH	COLOR	COUPLING SIZE	THREAD TYPE	COUPLING MATERIAL
8F	10 = 1" 15 = 1-1/2"	50 = 50' 100 = 100'	Y = Yellow WM = White (Mildew Treated)	10 = 1" 15 = 1-1/2"	N = NH I = IPT QT = Quarter Turn	Blank = Aluminum

Part Number Example: **8F10X50Y10N** = 8F Forestry Hose, 1" ID by 50' Length, Yellow, 1" Aluminum NH/NST Threaded Coupling

Construction:

Polyester Single Jacket
Polyurethane Inner Liner

Coating:

Mildew Treated (White Hose Only), Optional Dura-Cote™ (w/color)

Temperature Range:

-40° to 150°F (-40° to 65°C)

Coupling:


Aluminum NH/NST, IPT Threaded or Quarter Turn

Hose Colors:



Polyurethane Liner

Polyester Single Jacket



SIZE	SERVICE TEST	PROOF TEST	BURST	WEIGHT (For 50' Coupled)	BOWL SIZE
	PSI (kPa)	PSI (kPa)	PSI (kPa)	LBS (KG)	IN
1"	300 (2070)	600 (4140)	900 (6200)	5 (2.3)	1-5/32
1-1/2"	300 (2070)	600 (4140)	900 (6200)	7 (3.2)	1-3/4