

# Booster Hose - Type 2B

## Two-Braid Synthetic Rubber Booster Hose

### Performance Features:

Snap-tite 2B Booster hose is a high quality all-purpose fire engine booster hose product that can be charged while still on the reel.

Built to take rugged treatment, this hose has a red, synthetic rubber cover that resists abrasion while providing a smooth surface for easy handling. This hose is engineered to be dimensionally stable and will not flatten or crush on reels. This hose is designed to provide a constant working pressure up to 800 psi (5510 kPa) while staying flexible in temperatures as low as -40°F (40°C).

### How to Order

<b>2B</b>	<b>07X50</b>		<b>R</b>	<b>10</b>	<b>N</b>	<b>KP</b>
TYPE	HOSE I.D.	X HOSE LENGTH	COLOR	COUPLING SIZE	THREAD TYPE	COUPLING MATERIAL
2B	07 = 3/4" 10 = 1"	50 = 50' 100 = 100' 150 = 150' 200 = 200'	R = Red	10 = 1"	N = NH I = IPT	KP = Chrome Plated Brass Blank = Aluminum

Part Number Example: **2B07X50R10NKP** = 2B Hose, 3/4" ID by 50' Length, Red, 1" NH/NST Threaded Chrome Plated Coupling

### Construction:

Red Synthetic Rubber Cover  
Two High Strength Textile Braids  
Black Synthetic Rubber Liner

### Temperature Range:

-40° to 180°F (-40° to 80°C)

### Couplings Available:

Chrome Plated Brass or Aluminum  
NH/NST or IPT Threaded

### Hose Colors:



SIZE	SERVICE TEST	PROOF TEST	BURST	WEIGHT (For 50' Coupled)	BOWL SIZE
	PSI (kPa)	PSI (kPa)	PSI (kPa)	LBS (KG)	IN
3/4"	800 (5515)	1600 (11000)	2400 (16500)	52 (23.6)	1-1/4
1"	800 (5515)	1600 (11000)	2400 (16500)	70 (31.8)	1-19/32