

# LD - Type LD

## Lightweight Extruded Rubber Hose

### Performance Features

Snap-tite LD is a premium quality, nitrile rubber covered fire hose that is manufactured using a unique process which permanently bonds the nylon reinforcement to the nitrile rubber cover/liner. LD is an easily coiled, non-kinking, high flow, lightweight hose that also resists abrasion, chemicals and weathering by ozone. Extruded thru-the-weave construction means that no adhesives are used, therefore no delamination.

### How to Order

<b>LD</b> TYPE	<b>17X50</b> HOSE I.D. X HOSE LENGTH	<b>R</b> COLOR	<b>15</b> COUPLING SIZE	<b>N</b> THREAD TYPE	<b>BR</b> COUPLING MATERIAL
LD	10 = 1" 15 = 1-1/2" 17 = 1-3/4" 20 = 2" 25 = 2-1/2"	Y = Yellow R = Red K = Black B = Blue	10 = 1" 15 = 1-1/2" 20 = 2" 25 = 2-1/2"	N = NH I = IPT BW = British Instantaneous	Blank= Aluminum BR= Brass Rocker Lug BP= Brass Pin Lug G= Gunmetal (BW Thread only)

Part Number Example: **LD17X50R15NBR** = LD Hose, 1-3/4" ID by 50' Length, Red, 1-1/2" Brass Rocker Lug - NH/NST Threaded Coupling

### Construction:

Nitrile Rubber Cover  
& Liner w/Nylon Reinforcement

### Temperature Range:

-5° to 200°F (-20° to 95°C)

### Coupling:

Aluminum or Brass NH/NST  
or IPT Threaded,  
British Instantaneous

### Approvals:


Kitemark License KM 60099 to BS-6391 Type 3 Specification, ABS Type Approval, Meets Australian DEF (Aust)5195A and AS-2792-1992

### Hose Colors:



Nylon Fabric Reinforcement

Nitrile Rubber Thru-the-Weave



SIZE	SERVICE TEST	PROOF TEST	BURST	WEIGHT (For 50' coupled)	BOWL SIZE
	PSI (kPa)	PSI (kPa)	PSI (kPa)	LBS (KG)	IN
1"	250 (1725)	500 (3450)	770 (5310)	8 (3.6)	1-3/16
1-1/2"	250 (1725)	500 (3450)	770 (5310)	10 (4.5)	1-13/16
1-3/4"	250 (1725)	500 (3450)	770 (5310)	13 (5.9)	2-1/16
2"	250 (1725)	500 (3450)	770 (5310)	15 (6.8)	2-3/16
2-1/2"	250 (1725)	500 (3450)	770 (5310)	19 (8.3)	2-13/16

Operating Pressure not to Exceed 90% of Service Test Pressure