

Quik Draw™ - Type 2F

Light Duty Polyester Single Jacket Forestry Hose

Performance Features:

Quik Draw™ is a small diameter, lightweight, compact single jacket fire hose using standard 3/4" brass Garden Hose Thread (GHT) fittings having a working pressure of 150 psi (1030 kPa). This high tenacity filament polyester, polyurethane lined hose can be ordered with or without Snap-tite's Dura-Cote™ treatment that minimizes abrasion and pin-holing. With 50' of Quik-Draw™ weighing only 1.25 lbs and a coil diameter of around 9 inches, this hose can be taken almost anywhere.

How to Order

2F	06X50	W	07	GH	B
TYPE	HOSE I.D. x HOSE LENGTH	COLOR	COUPLING SIZE	THREAD TYPE	COUPLING MATERIAL
2F	06 = 5/8" x 50 = 50'	Y = Yellow W=White (Uncoated)	07 = 3/4"	GH = Garden Hose	B= Brass

Part Number Example: **2F06X50W07GHB** = 2F Quik Draw Forestry Hose, 5/8" ID by 50' Length, White, 3/4" Brass Garden Hose Threaded Coupling

Construction:

Polyester Single Jacket
Polyurethane Lined Hose

Coating:

Optional Dura-Cote™ (w/color)


Temperature Range:

-40° to 150°F (-40° to 65°C)

Couplings Available:

Brass Garden Hose


Hose Colors:



FORESTRY



C.A.F.S.



SIZE	MAX. OPERATING PRESSURE	BURST	WEIGHT
	PSI (kPa)	PSI (kPa)	(For 50' Coupled) LBS (KG)
5/8"	150 (1035)	600 (4140)	1.25 (0.6)